

E-Cigarette Aerosol Analysis Report

Report No. : TCT200528C903

Date : Jun. 05, 2020

Page No.: 1 of 6

Applicant: GEEKVAPE TECHNOLOGY CO., LTD.**Address:** 7th Floor,#3 west Block, LaoBing Building, XingYe Rd#3012, Bao'an District, Shenzhen, Guangdong, China**The following sample was submitted and identified by/on behalf of the client as:**

Sample Name: GEEKVAPE AEGIS HERO POD

Model No.: AEGIS HERO POD

Tank: 4.0ml

Coil: 1: 0.4ohm KA1 2: 0.6ohm KA1

Power level in testing: 1: 20W 2: 20W

Adjustable air inlet or not: Yes

Trade Mark: GEEKVAPE

Sample Received Date: 2020.05.28

Testing Period: 2020.05.28—2020.06.05

Test Method: Please refer to the following page(s).

Test Result(s): Please refer to the following page(s).

Remark: Test data of this report was extracted from report No. TCT200528C018.

Test Items		Test Requested
1	Carbonyl Compounds: Formaldehyde, Acetaldehyde, Acrolein, Crotonaldehyde	Emission testing according to Article 20 of Tobacco Product Directive (2014/40/EU)
2	Metals: Aluminum, Chromium, Iron, Nickel, Tin, Lead, Cadmium, Arsenic, Antimony	
3	Nicotine consistency	

Checked by



Noel Yin

Signed for and on behalf of TCT



Kim Zhang

Technical Manager



E-Cigarette Aerosol Analysis Report

Report No. : TCT200528C903

Date : Jun. 05, 2020

Page No.: 2 of 6

Test Results:

Test Condition for test items except Nicotine consistency test:

With reference to the CORESTA RECOMMENDED METHOD N° 81 method parameter, Afnor standardization XP D90-300-3, International Standard ISO 20768:2018 and PD CEN/TR 17236:2018, a smoke machine was used to collect the vapor.

Puff Duration	3.0s±0.1s
Puff Volume	55mL±0.3mL
Puff Frequency	30s±0.5s
Puff of Each Group	20
Group Interval Time	300s±120s
Maximum Flow	18.5mL/s±1.0mL/s
Pressure Drop	< 50hPa
Group	5
Total Number of Puff	100
Total Duration of Vaporization	300s

The temperature and relative humidity of the test atmosphere during machine preparation and testing were kept within the following limits: temperature ±2℃, relative humidity ±5%

Sample Description:

No.1 GEEKVAPE AEGIS HERO POD with 0.4ohm KA1

No.2 GEEKVAPE AEGIS HERO POD with 0.6ohm KA1

E-Cigarette Aerosol Analysis Report

Report No. : TCT200528C903

Date : Jun. 05, 2020

Page No.: 3 of 6

1. Carbonyl Compounds Content(s)

Method: The volatile aldehydes are extracted from the aerosol by bubbling each puff through an impactor containing an acidified aqueous solution of 2,4-DNPH. The samples are analyzed by reverse phase high-performance liquid chromatography and determined using a UV detector.

Test Item	CAS No.	Unit	MDL	LOQ	Content(s)	
					No.1	No.2
Formaldehyde	50-00-0	ug/100puffs	0.667	2	9.72	11.2
Acetaldehyde	75-07-0	ug/100puffs	0.667	2	2.04	2.80
Acrolein	107-02-8	ug/100puffs	0.667	2	ND	ND
Crotonaldehyde	4170-30-3	ug/100puffs	0.667	2	ND	ND

- Note:
- ug = Microgram
 - ND = Not Detected (lower than MDL)
 - MDL = Method Detection Limit
 - LOQ = Limit of Quantitation
 - E-Liquid Used: E-liquid B (AFNOR XP D90-300-3)

E-Cigarette Aerosol Analysis Report

Report No. : TCT200528C903

Date : Jun. 05, 2020

Page No.: 4 of 6

2. Metals Content(s)

Method: With reference to Afnor XP D90-300-3, the aerosol was absorbed using a Cambridge filter, and the Cambridge filter was removed and placed in an Erlenmeyer flask, added to 20 mL of 5%(v/v) Nitric acid solution, shaken at 210 rpm for 60 min, filtered, and analyzed by ICP-MS.

Test Item	CAS No.	Unit	MDL	LOQ	Content(s)	
					No.1	No.2
Aluminum(Al)	7429-90-5	ug/100puffs	0.025	0.25	ND	ND
Chromium(Cr)	7440-47-3	ug/100puffs	0.005	0.05	ND	ND
Iron(Fe)	7439-89-6	ug/100puffs	0.005	0.05	ND	ND
Nickel(Ni)	7440-02-0	ug/100puffs	0.025	0.25	ND	ND
Tin(Sn)	7440-31-5	ug/100puffs	0.25	2.5	ND	ND
Lead(Pb)	7439-92-1	ug/100puffs	0.025	0.25	ND	ND
Cadmium(Cd)	7440-43-9	ug/100puffs	0.005	0.05	ND	ND
Arsenic(As)	7440-38-2	ug/100puffs	0.025	0.25	ND	ND
Antimony(Sb)	7440-36-0	ug/100puffs	0.025	0.25	ND	ND

- Note:
- ug = Microgram
 - ND = Not Detected (lower than MDL)
 - MDL = Method Detection Limit
 - LOQ = Limit of Quantitation
 - E-Liquid Used: E-liquid B (AFNOR XP D90-300-3)

E-Cigarette Aerosol Analysis Report

Report No. : TCT200528C903

Date : Jun. 05, 2020

Page No.: 5 of 6

3. Nicotine Consistency Test

Test Condition: With reference to the CORESTA RECOMMENDED METHOD N° 81 method parameter and Afnor standardization XP D90-300-3, a smoke machine was used to collect the vapor.

Puff Duration	3.0s±0.1s
Puff Volume	55mL±0.3mL
Puff of Each Group	20
Maximum Flow	18.5mL/s±1.0mL/s
Pressure Drop	< 50hPa

The temperature and relative humidity of the test atmosphere during machine preparation and testing were kept within the following limits: temperature $\pm 2^{\circ}\text{C}$, relative humidity $\pm 5\%$

Method: A reference liquid was prepared. A pharmaceutical nicotine inhaler was used as a comparator. Products were attached to a smoke machine, and the aerosol was collected in Cambridge filter pads. After trapping and solvent extraction, solution was analyzed by GC-MS and nicotine was dosed by comparing the areas obtained on the MS detector with those of standard solutions prepared in the laboratory under concentration conditions surrounding those of the samples.

Sample No.	Nicotine(CAS No.:54-11-5) Contents(mg/20Puffs)						Total (mg/100puffs)
	Group 1*	Group 2	Group 3*	Group 4	Group 5*	AVG	
No.1	1.89	1.86	1.89	1.86	1.85	1.87	9.36
Deviation(%)	0.8	-	0.9	-	0.9	-	-

Sample No.	Nicotine(CAS No.:54-11-5) Contents(mg/20Puffs)						Total (mg/100puffs)
	Group 1*	Group 2	Group 3*	Group 4	Group 5*	AVG	
No.2	2.18	2.21	2.22	2.21	2.23	2.21	11.1
Deviation(%)	1.4	-	0.4	-	1.1	-	-

- Note:
- mg = milligram
 - ND = Not Detected (lower than MDL)
 - MDL = Method Detection Limit = 0.01mg/20Puffs
 - LOQ = Limit of Quantitation = 0.1mg/20Puffs
 - 1group = 20puffs
 - * Values used for determination of consistency of nicotine emission
 - E-Liquid Used: E-liquid A (AFNOR XP D90-300-3)
 - Under the conditions of the test and with reference to AFNOR XP D90-300-3, the electronic cigarette delivers a dose of nicotine at consistent levels.

E-Cigarette Aerosol Analysis Report

Report No. : TCT200528C903

Date : Jun. 05, 2020

Page No.: 6 of 6

Photo(s) of the sample(s)



GEEKVAPE AEGIS HERO POD with 0.4ohm KA1/0.6ohm KA1

***** End of Report *****

Remark: This report is considered invalidated without the Special Seal for Inspection of the TCT. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of TCT, this test report shall not be copied except in full and published as advertisement.